
WRENCH SERIES



Heavy Adjustable Wrench






Item NO.	Size	L Middle length	B Head width	Z Jaw opening	D Opening depth	H Head thickness	B1 Tail width			RMB
CL404306	6"	154.00	49.00	22.03	22.03	11.65	19.86	6/120	0.13	
CL404308	8"	203.00	58.00	27.98	27.98	13.05	24.14	6/120	0.23	
CL404310	10"							6/60	0.37	
CL404312	12"	303.00	83.00	37.98	37.98	18.05	31.72	6/36	0.63	
CL404315	15"	379.00	96.00	48.34	48.34	20.26	34.88	2/20	1.27	

- Alloy steel forging, integral heat treatment, hardness in HRC42~46°
- The head is fine polished, the surface is chrome plated, wear-resistant and rust-resistant
- Precision machining of spanner, flexible opening, stable spanner and large torque

Adjustable Wrench






Item NO.	Size	L Middle length	B Head width	Z Jaw opening	D Opening depth	H Head thickness	B1 Tail width			RMB
CL400204	4"	107.00	33.00	15.54	12.48	8.32	14.38	12/240	0.05	
CL400206	6"	151.00	45.00	20.66	18.37	11.87	18.86	6/120	0.13	
CL400208	8"	205.00	59.00	27.05	23.82	13.72	24.09	6/60	0.25	
CL400210	10"	253.00	68.00	32.74	31.06	16.65	27.15	6/60	0.45	
CL400212	12"	301.00	80.00	37.31	33.07	20.27	31.54	6/36	0.70	

- Alloy steel forging, integral heat treatment, hardness in HRC42~46°
- The head is fine polished,the surface is chrome plated, wear-resistant and rust-resistant
- Precision machining of spanner, flexible opening, stable spanner and large torque
- With precise calibration size under the opening, improve working efficiency

Plastic Handle Adjustable Wrench






Item NO.	Size	L Middle length	B Head width	Z Jaw opening	D Opening depth	H Head thickness	B1 Tail width			RMB
CL404108	8"	160.00	49.00	25.09	21.61	10.47	24.97	6/60	0.14	
CL404110	10"	263.00	71.00	37.05	31.55	16.86	38.10	6/48	0.52	
CL404112	12"	308.00	83.00	42.76	35.78	18.42	38.26	6/36	0.69	

- The head is fine polished, the surface is chrome plated, wear-resistant and rust-resistant
- Precision machining of spanner, flexible opening, stable spanner and large torque
- The quincunx hole with hexagonal square hole tail can be used as quincunx spanner
- Plastic-coated handle, comfortable to hold

Adjustable Wrench






Item NO.	Size	L Middle length	B Head width	Z Jaw opening	D Opening depth	H Head thickness	B1 Tail width			RMB
CL400215	15"	376.00	103.00	50.43	42.98	25.28	25.72	2/18	1.41	
CL400218	18"	450.00	123.00	61.38	51.35	28.21	29.08	2/12	2.08	
CL400224	24"	600.00	144.00	70.22	61.58	32.30	35.78	1/4	3.61	
CL400230	30"	778.00	176.00	91.00	78.00	33.41	36.20	1/3	5.92	

- Carbon steel forging, integral heat treatment, hardness in HRC42~46°
- Precision machining of pulling mouth, integral forging of pulling body,
- Precise calibration, exquisite worm gear, open and close freely

Pipe And Adjustable Wrench





Item NO.	Size	L Middle length	B Head width	Z Jaw opening	D Opening depth	H Head thickness	B1 Tail width			RMB
CL404908	8"	212.00	60.00	32.76	26.24	14.96	22.26	6/60	0.33	
CL404910	10"	262.00	70.00	41.48	30.71	16.44	28.15	6/48	0.49	
CL404912	12"	312.00	88.00	50.34	35.55	19.34	33.58	6/36	0.77	

- Alloy steel forging, overall heat treatment including worm gear at HRC42~46°
- The head is fine polished, the surface is chrome plated, wear-resistant and rust-resistant
- The pulling mouth is precisely machined and can also be used as pipe pliers.
  The pulling mouth is in gear shape.
- The quincunx hole with hexagonal square hole tail can be used as quincunx spanner

Adjustable Wrench Black Nickel Square Hole




Item NO.	Size			RMB
CL407710	10"	6/60		
CL407712	12"	6/36		

- Alloy steel forging, overall heat treatment, sturdy and durable.
- Polished head, surface coated with black nickel, wear-resistant and rust proof.
- The square hole design at the tail facilitates suspension and storage.
- Precision machining of the trigger, flexible opening, stable trigger, and high torque
- Laser precise calibration improves work efficiency

VDE
绝缘

Large Opening Light Adjustable Wrench






Item NO.	Size	L Middle length	B Head width	Z Nose projection	D Opening depth	H Head thickness	B1 Tail width			RMB
CL407106	6"	119.00	44.00	26.56	22.02	11.38	23.78	6/120	0.10	
CL407108	8"	145.00	55.00	31.14	31.78	12.97	27.78	6/96	0.15	
CL407110	10"	161.00	68.00	38.93	34.01	15.26	30.20	6/60	0.27	
CL407112	12"	210.00	86.00	46.72	42.34	18.25	36.30	6/36	0.47	

- Alloy steel forging, integral heat treatment, hardness in HRC42~46°
- The head is fine polished, the surface is chrome plated, wear-resistant and rust-resistant
- Precision machining of spanner, flexible opening, stable spanner and large torque
- The weight is 30% lighter than the standard wrench of the same scale, with good handle and not easy to fatigue.
- Suitable for small space, mechanical maintenance, car repair, bathroom air conditioning installation, convenient and lexible, easy to keep

Right Angle Spanner






Item NO.	Size	L Middle length	B Head width	Z Nose projection	D Opening depth	H Head thickness	B1 Tail width			RMB
CL404509	9"	238.00	65.00	64.00	36.00	16.09	18.94	5/30	0.49	
CL404511	11"	284.00	76.00	79.00	44.00	18.23	22.64	6/36	0.67	
CL404515	15"	375.00	85.00	85.00	46.00	21.57	31.12	2/12	1.55	

- Alloy steel forging, overall heat treatment including worm gear at HRC42~46°
- The head is fine polished, the surface is chrome plated, wear- resistant and rust-resistant
- The pulling mouth is precisely machined and can also be used as pipe pliers. The pulling mouth is in gear shape.
- The quincunx hole with hexagonal square hole tail can be used as quincunx spanner

Four Multi-purpose Wrench





Item NO.	Size	L Middle length	B Head width	Z Nose projection	D Opening depth	H Head thickness	B1 Tail width			RMB
CL405816	16"	409.00	90.00	47.00	36.00	18.74	6.58	6/24	1.04	


- Alloy steel forging, integral heat treatment, hardness in HRC42~46°
- Precision machining of pulling mouth and integral forging of pulling body
- The head can be detachable with open wrench in front and pipe wrench in back, making it flexible and convenient to use
- The protruding part of the spanner head can be knocked
- Tail taper design, can replace the use of ordinary small crowbar



Double Open End Spanner



Item NO.	Size		RMB
CL401106	6x7mm	10/500	
CL401108	8x10mm	10/250	
CL401109	9x11mm	10/250	
CL401110	10x12mm	10/250	
CL401111	11x13mm	10/200	
CL401112	12x14mm	10/200	
CL401113	13x15mm	10/200	
CL401114	14x17mm	10/250	
CL401116	13x16mm	10/250	
CL401118	16x18mm	10/200	
CL401119	17x19mm	10/100	
CL401120	19X21mm	10/100	
CL401121	18x21mm	10/100	
CL401122	19x22mm	10/100	
CL401124	22x24mm	10/100	
CL401127	24x27mm	5/50	
CL401130	27x30mm	5/50	
CL401132	30x32mm	5/50	
CL401134	32x34mm	5/20	
CL401136	34x36mm	5/20	




Size	L	D1	C1	D2	C2	B	H	W kg
6x7	123	12.20	5.44	14.15	5.46	7.17	3.55	0.025
8x10	142	16.48	5.38	20.61	5.30	8.75	3.58	0.040
9x11	160	20.60	6.28	24.41	6.20	10.42	4.00	0.060
10x12	160	20.28	5.88	24.29	5.90	10.14	3.60	0.050
11x13	179	24.28	6.34	29.50	6.58	11.83	4.22	0.080
12x14	178	24.60	6.27	29.54	6.34	11.67	3.88	0.070
13x15	187	29.17	7.12	31.18	6.99	13.65	4.20	0.100
14x17	197	29.40	7.29	35.61	7.41	12.91	4.30	0.115
13x16	186	29.42	7.14	31.27	7.22	12.75	4.80	0.105
16x18	196	33.40	7.52	35.20	7.14	13.45	4.37	0.120
17x19	218	35.38	8.24	38.64	8.30	15.65	5.61	0.175
19X21	239	38.49	9.14	44.34	9.03	17.93	6.60	0.250
18x21	240	38.65	9.07	44.14	9.20	17.74	6.05	0.235
19x22	241	38.04	8.76	43.18	8.90	18.08	6.11	0.235
22x24	261	44.22	9.72	49.06	9.57	18.74	7.14	0.325
24x27	283	48.44	10.12	54.94	9.87	21.65	7.00	0.395
27x30	296	56.05	10.71	61.91	10.55	23.84	7.42	0.505
30x32	309	62.30	11.33	66.25	11.44	26.46	8.68	0.650
32x34	315	68.39	12.53	75.72	12.24	29.24	8.55	0.750
34x36	315	67.77	12.68	75.14	12.48	28.44	8.95	0.730

- Forged with chromium vanadium steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts
- American standard plus long style, labor saving and more durable

Bi-hexagonal Ring Spanner



Item NO.	Size		RMB
CL400906	6X7mm	10/500	
CL400955	5.5x7mm	10/500	
CL400908	8x10mm	10/500	
CL400909	9x11mm	10/250	
CL400910	10x12mm	10/250	
CL400911	11x13mm	10/250	
CL400912	12x14mm	5/200	
CL400913	13x15mm	5/200	
CL400914	14x17mm	5/200	
CL400916	13x16mm	5/200	
CL400918	16x18mm	5/100	
CL400919	17x19mm	5/100	
CL400920	19X21mm	5/100	
CL400921	18x21mm	5/100	
CL400922	19x22mm	5/100	
CL400924	22x24mm	5/100	
CL400927	24x27mm	5/50	
CL400930	27x30mm	5/50	
CL400932	30x32mm	5/50	
CL400934	32x34mm	5/20	
CL400936	34x36mm	5/20	
CL400941	36X41mm	5/20	
CL400946	41X46mm	5/20	
CL400950	46X50mm	3/12	
CL400960	50X55mm	3/12	



Size	L	A	C	D	B	W kg
5.5x7	160	11.13	5.44	6.04	12.23	0.045
6X7	162	10.92	5.35	5.81	11.61	0.045
8x10	175	14.10	6.35	6.49	16.22	0.060
9x11	190	15.53	7.17	7.81	18.60	0.090
10x12	192	16.09	7.19	7.77	19.09	0.100
11x13	205	18.81	7.25	8.50	22.11	0.125
12x14	205	19.13	8.16	8.41	22.34	0.110
13x15	225	22.50	8.52	9.00	24.10	0.135
14x17	228	21.95	8.77	9.30	25.41	0.150
13x16	225	21.81	9.00	9.22	23.64	0.145
16x18	225	24.53	9.10	9.18	25.95	0.145
17x19	245	26.18	9.52	10.40	28.81	0.200
18x21	265	28.83	10.22	11.13	32.80	0.255
19x22	265	29.80	11.58	11.68	34.32	0.285
22x24	292	33.92	11.96	12.35	37.20	0.340
24x27	348	36.02	12.27	13.15	40.35	0.500
27x30	392	40.97	14.90	15.07	45.40	0.650
30x32	400	45.40	13.69	13.89	47.80	0.665
32x34	425	47.72	18.14	17.36	51.86	0.820
34x36	427	49.13	16.31	17.58	52.81	0.815
36X41	450	58.53	18.50	18.84	66.54	1.375
41X46	490	60.80	22.31	23.74	65.80	1.900
46X50	525	71.00	22.65	22.66	77.15	2.105
50X55	545	73.08	24.62	24.95	79.18	2.470

- Forged with chromium vanadium steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes
- American standard plus long style, labor saving and more durable

VDE 绝缘

Combination Spanner



ANSI ISO Cr-V

Item NO.	Size		RMB
CL401006	6mm	10/500	
CL401007	7mm	10/500	
CL401008	8mm	10/500	
CL401009	9mm	10/500	
CL401010	10mm	10/500	
CL401011	11mm	10/200	
CL401012	12mm	10/200	
CL401013	13mm	10/200	
CL401014	14mm	5/200	
CL401015	15mm	5/200	
CL401016	16mm	5/200	
CL401017	17mm	5/100	
CL401018	18mm	5/100	
CL401019	19mm	5/100	
CL401020	20mm	5/80	
CL401021	21mm	5/100	
CL401022	22mm	5/100	
CL401023	23mm	5/60	
CL401024	24mm	5/50	
CL401025	25mm	5/50	
CL401026	26mm	5/50	
CL401027	27mm	5/50	
CL401028	28mm	5/50	
CL401030	30mm	5/50	
CL401032	32mm	5/50	
CL401034	34mm	5/20	
CL401036	36mm	5/20	



Size	L	D	C	B	A	H	T	W kg
6mm	125	13.55	5.35	10.85	5.77	7.06	3.55	0.025
7mm	126	13.38	4.79	11.83	5.51	6.56	3.21	0.020
8mm	140	16.33	5.12	13.38	6.12	7.87	3.36	0.030
9mm	149	18.23	5.22	14.70	6.43	86.90	3.59	0.035
10mm	158	20.46	5.85	15.98	7.04	9.56	3.81	0.045
11mm	165	22.25	6.58	18.32	7.58	11.41	4.35	0.065
12mm	170	24.66	6.34	19.01	8.01	11.34	4.17	0.065
13mm	175	26.34	6.53	19.52	8.26	12.17	4.40	0.075
14mm	188	28.73	7.07	21.91	8.78	12.73	4.53	0.090
15mm	197	31.50	7.22	23.16	9.09	13.73	4.88	0.110
16mm	207	32..92	7.23	24.90	9.34	14.07	4.94	0.120
17mm	224	35.00	7.92	26.62	10.60	14.61	5.42	0.150
18mm	234	37.30	8.07	27.37	10.25	15.00	5.36	0.160
19mm	247	38.72	8.28	28.77	10.72	16.50	5.88	0.195
20mm	247	38.63	7.80	27.86	10.80	16.84	5.34	0.180
21mm	273	43.14	8.90	30.64	11.60	18.13	6.25	0.245
22mm	291	44.90	9.05	32.70	11.07	19.01	6.00	0.270
23mm	292	44.87	9.38	32.58	11.10	19.44	5.78	0.275
24mm	312	49.77	10.04	35.05	13.00	21.54	7.21	0.385
25mm	323	51.94	9.87	36.57	13.30	22.21	6.95	0.400
26mm	321	53.45	9.84	38.46	12.87	21.83	6.91	0.410
27mm	334	56.09	10.95	39.33	13.61	21.94	7.59	0.460
28mm	334	56.00	11.04	39.61	13.85	22.15	7.84	0.470
30mm	350	61.67	10.88	44.65	14.14	23.47	7.78	0.545
32mm	370	65.29	11.91	47.10	15.31	24.27	8.27	0.640
34mm	451	72.61	13.08	52.87	17.67	28.05	9.22	1.010
36mm	450	72.15	13.42	53.14	17.96	27.87	9.61	0.980

- Forged with chromium vanadium steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- Bend the head 15° for easy fastening of dented hex bolts and nuts
- American standard plus long style, labor saving and more durable

Double Open End Spanner



DIN ISO

Item NO.	Size		RMB
CL405106	6X7mm	10/500	
CL405108	8X10mm	10/500	
CL405109	9X11mm	10/300	
CL405110	10X12mm	10/300	
CL405112	12X14mm	10/300	
CL405113	13X15mm	10/200	
CL405114	14X17mm	10/200	
CL405116	13X16mm	10/200	
CL405118	16X18mm	10/200	
CL405119	17X19mm	5/100	
CL405121	18X21mm	5/100	
CL405122	19X22mm	5/100	
CL405124	22X24mm	5/100	
CL405127	24X27mm	5/100	
CL405130	27X30mm	5/50	
CL405132	30X32mm	5/50	

- Forged by high carbon steel, hardness HRC42~45°
- For quick removal and fastening of hexagon bolts and nuts

Bi-hexagonal Ring Spanner



DIN ISO

Item NO.	Size		RMB
CL405206	6X7mm	10/300	
CL405208	8X10mm	10/300	
CL405209	9X11mm	10/200	
CL405210	10X12mm	10/200	
CL405212	12X14mm	5/250	
CL405213	13X15mm	5/150	
CL405214	14X17mm	5/150	
CL405216	13X16mm	5/150	
CL405218	16X18mm	5/150	
CL405219	17X19mm	5/100	
CL405221	18X21mm	5/100	
CL405222	19X22mm	5/100	
CL405224	22X24mm	5/60	
CL405227	24X27mm	5/60	
CL405230	27X30mm	5/60	
CL405232	30X32mm	5/60	

- Forged by high carbon steel, hardness HRC42~45°
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes

Combination Spanner



Item NO.	Size		RMB
CL405306	6mm	10/500	
CL405307	7mm	10/500	
CL405308	8mm	10/300	
CL405309	9mm	10/300	
CL405310	10mm	10/300	
CL405311	11mm	10/300	
CL405312	12mm	10/300	
CL405313	13mm	10/300	
CL405314	14mm	5/100	
CL405315	15mm	5/100	
CL405316	16mm	5/100	
CL405317	17mm	5/100	
CL405318	18mm	5/100	
CL405319	19mm	5/100	
CL405321	21mm	5/100	
CL405322	22mm	5/100	
CL405323	23mm	5/100	
CL405324	24mm	5/60	
CL405327	27mm	5/60	
CL405330	30mm	5/60	
CL405332	32mm	5/60	


- Conforms to DIN 3113 ISO 3318 Type A standard
- Forged by high carbon steel, hardness HRC42~45°
- Bend the head 15° for easy fastening of dented hex bolts and nuts



Double Open End Spanner



Item NO.	Size		RMB
CL410855	5.5X7mm	10/500	
CL410806	6X7mm	10/500	
CL410808	8X10mm	10/500	
CL410809	9X11mm	10/500	
CL410810	10X12mm	10/250	
CL410811	11X13mm	10/250	
CL410812	12X14mm	10/250	
CL410813	13X15mm	10/250	
CL410814	14X17mm	10/250	
CL410816	13X16mm	10/250	
CL410818	16X18mm	10/250	
CL410819	17X19mm	10/150	
CL410821	18X21mm	10/150	
CL410822	19X22mm	10/150	
CL410824	22X24mm	5/60	
CL410827	24X27mm	5/60	
CL410830	27X30mm	5/60	
CL410832	30X32mm	5/40	
CL410834	32X34mm	5/40	
CL410836	32X36mm	5/40	
CL410841	36X41mm	5/30	



Size	L	D1	C1	D2	C2	B	H	W kg
5.5*7	111	16.34	4.23	18.51	4.02	9.44	3.07	0.025
6*7	111	16.40	4.15	18.40	4.14	9.46	2.97	0.025
8*10	125	19.71	4.36	22.58	4.61	10.46	3.49	0.035
9*11	137	22.92	5.10	26.10	5.17	11.95	3.62	0.050
10*12	138	23.24	5.20	26.32	5.25	12.10	3.86	0.055
11*13	145	25.88	5.60	28.90	5.45	12.18	3.68	0.060
12*14	153	27.72	5.45	31.64	5.38	13.66	3.55	0.070
13*15	156	28.00	5.59	32.96	5.71	13.81	3.95	0.075
14*17	168	31.35	6.12	36.51	6.07	15.25	4.26	0.100
13*16	157	27.88	6.07	32.85	5.92	13.65	4.07	0.080
16*18	175	32.87	6.25	37.04	6.21	14.91	4.46	0.105
17*19	188	36.11	7.25	40.25	7.36	16.54	5.36	0.150
18*21	193	36.56	7.28	42.51	7.52	17.50	5.16	0.160
19*22	210	40.05	7.45	44.65	7.68	18.57	5.33	0.185
22*24	230	44.54	8.43	49.60	8.34	19.92	6.26	0.245
24*27	250	49.95	8.98	54.91	8.79	21.86	6.94	0.335
27*30	264	54.60	9.54	58.43	9.55	23.88	6.94	0.390
30*32	278	57.36	10.13	63.39	10.25	25.61	7.32	0.465
32*34	303	65.34	11.77	69.08	11.82	28.73	8.64	0.675
32*36	303	65.50	11.46	69.21	11.50	28.75	8.50	0.650
36*41	325	73.14	12.55	80.04	12.04	32.90	8.79	0.850


- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment.
- For quick removal and fastening of hexagon bolts and nuts

VDE 绝缘

Bi-hexagonal Ring Spanner



Item NO.	Size		RMB
CL410606	6X7mm	10/500	
CL410608	8X10mm	10/500	
CL410609	9X11mm	10/280	
CL410610	10X12mm	10/280	
CL410611	11X13mm	10/280	
CL410612	12X14mm	10/280	
CL410613	13X15mm	5/180	
CL410614	14X17mm	5/180	
CL410616	13X16mm	5/200	
CL410618	16X18mm	5/150	
CL410619	17X19mm	5/150	
CL410621	18X21mm	5/100	
CL410622	19X22mm	5/100	
CL410624	22X24mm	5/100	
CL410627	24X27mm	5/60	
CL410630	27X30mm	5/60	
CL410632	30X32mm	5/60	
CL410634	32X34mm	5/40	
CL410636	32X36mm	5/40	
CL410641	36X41mm	5/20	
CL410655	5.5X7mm	10/500	



Size	L	A	C	D	B	W kg
5.5*7	121	11.17	4.74	4.71	12.69	0.025
6*7	122	11.23	4.75	5.47	12.66	0.025
8*10	140	14.37	5.24	6.09	16.96	0.040
9*11	160	14.85	6.45	6.97	16.83	0.050
10*12	164	16.73	6.85	7.02	19.11	0.060
11*13	190	19.17	8.22	7.93	21.97	0.075
12*14	190	19.64	6.67	6.96	21.67	0.080
13*15	190	20.34	7.30	7.82	24.25	0.085
14*17	220	22.06	9.10	9.03	26.03	0.135
13*16	217	21.99	8.55	8.47	25.59	0.130
16*18	222	24.52	8.21	9.05	27.07	0.130
17*19	252	25.26	9.51	10.12	28.58	0.185
18*21	255	26.80	9.59	9.49	31.35	0.185
19*22	295	29.21	10.39	10.53	32.82	0.240
22*24	297	32.47	10.30	10.55	34.67	0.270
24*27	345	35.85	10.92	12.01	39.18	0.375
27*30	372	39.82	12.30	12.95	44.34	0.530
30*32	400	44.28	13.96	14.42	47.05	0.605
32*34	420	47.52	15.90	17.94	52.61	0.820
32*36	420	47.07	15.38	16.63	53.31	0.775
36*41	455	53.04	17.46	17.96	59.93	1.055

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes

Combination Spanner



Item NO.	Size		RMB
CL410706	6mm	10/500	
CL410707	7mm	10/500	
CL410708	8mm	10/500	
CL410709	9mm	10/500	
CL410710	10mm	10/500	
CL410711	11mm	10/500	
CL410712	12mm	10/250	
CL410713	13mm	10/250	
CL410714	14mm	10/150	
CL410715	15mm	10/150	
CL410716	16mm	10/150	
CL410717	17mm	10/150	
CL410718	18mm	10/150	
CL410719	19mm	10/150	
CL410721	21mm	5/60	
CL410722	22mm	5/60	
CL410724	24mm	5/60	
CL410727	27mm	5/60	
CL410730	30mm	5/30	
CL410732	32mm	5/30	
CL410734	34mm	5/30	
CL410736	36mm	5/20	
CL403241	41mm	3/12	
CL403246	46mm	3/12	
CL403250	50mm	10	
CL403255	55mm	10	
CL403260	60mm	8	
CL403265	65mm	8	



Size	L	D	C	B	A	H	T	W kg
6mm	101	14.06	4.08	11.30	4.64	7.61	3.00	0.020
7mm	122	15.78	4.58	12.72	4.95	7.92	3.18	0.025
8mm	125	17.68	5.45	14.27	5.84	9.06	3.74	0.035
9mm	129	19.06	5.64	15.66	6.37	10.08	4.09	0.040
10mm	142	21.50	5.57	16.15	6.45	10.54	3.75	0.045
11mm	153	23.16	6.04	17.46	7.11	10.63	3.91	0.055
12mm	162	25.33	6.26	18.86	7.35	11.44	4.13	0.065
13mm	174	27.60	6.67	20.08	7.87	12.26	4.64	0.080
14mm	183	29.87	6.82	21.61	7.47	12.96	4.35	0.090
15mm	183	32.17	6.76	23.94	8.40	13.71	4.16	0.095
16mm	195	34.49	7.26	25.09	8.43	13.65	4.41	0.110
17mm	208	35.74	6.88	26.87	8.94	14.69	4.45	0.125
18mm	218	37.29	7.18	27.36	9.10	15.10	4.59	0.140
19mm	230	39.84	7.45	28.21	9.87	16.60	4.81	0.160
21mm	251	42.83	7.97	31.92	10.92	18.00	5.28	0.215
22mm	263	44.38	8.26	32.97	11.46	18.36	5.77	0.235
24mm	292	49.02	8.72	36.02	11.05	20.07	5.90	0.295
27mm	318	54.66	9.52	40.22	11.81	21.80	6.56	0.380
30mm	342	58.99	9.99	43.70	12.71	22.95	6.89	0.460
32mm	355	63.61	10.96	46.52	13.80	23.73	6.96	0.545
34mm	387	66.71	11.64	51.09	14.36	26.07	7.66	0.705
36mm	411	69.96	11.48	55.77	15.40	28.31	8.20	0.835

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- The quincunx is designed with a 12-angle shape for easy fastening of sunken hexagonal bolts and nuts

Bi-hexagonal Ring Spanner Set



ANSI ISO Cr-V

Item NO.	Size		KG	RMB
CL401208	6X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24mm	15	1.53	
CL401210	6X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	6	2.75	
CL401212	6X7,8X10,9X11,10X12,11X13,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	6	3.06	

- Forged with chromium vanadium steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes

Double Open End Spanner Set



ANSI ISO Cr-V

Item NO.	Size		KG	RMB
CL401408	6X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24mm	8	1.30	
CL401410	6X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	8	2.42	
CL401412	6X7,8X10,9X11,10X12,11X13,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	10	2.64	
CL401414	6X7,8X10,9X11,10X12,11X13,13X15,12X14,14X17,16X18,17X19,19X22,22X24,24X27,30X32mm	4	2.86	

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- The quincunx is designed with a 12-angle shape for easy fastening of sunken hexagonal bolts and nuts

Double Open End Spanner Set



DIN ISO

Item NO.	Size		KG	RMB
CL403608	6X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24mm	20	0.93	
CL403610	5.5X7,8X10,10X12,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	12	1.83	
CL403612	6X7,8X10,9X11,10X12,11X13,12X14,14X17,17X19,19X22,22X24,24X27,30X32mm	12	1.90	

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts

Combination Spanner Set



ANSI ISO Cr-V

Item NO.	Size		KG	RMB
CL401308	8,9,10,12,13,14,17,19mm	6	0.90	
CL401310	8,9,10,11,12,13,14,17,19,22mm	10	1.45	
CL401312	6,7,8,9,10,11,12,13,14,17,19,22mm	12	1.53	
CL401314A	8,9,10,11,12,13,14,17,19,21,24,27,30,32mm	6	2.15	

- Forged with chromium vanadium steel, hardness HRC42~45°
- Mirror polishing chrome plating rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts

Combination Spanner Set



Item NO.	Size			RMB
CL403508	8、9、10、12、13、14、17、19mm	20	0.76	
CL403510	8、9、10、11、12、13、14、17、19、22mm	8	1.18	
CL403512	6、7、8、9、10、11、12、13、14、17、19、22mm	6	1.22	
CL403514A	8、9、10、11、12、13、14、17、19、21、24、27、30、32mm	12	2.81	
CL403514B	8、9、10、11、12、13、14、15、16、17、18、19、22、24mm	12	1.84	

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- Bend the head 15° for easy fastening of dented hex bolts and nuts

Electrophoresis Double Headed Wrench Set



Item NO.	Size			RMB
CL405508	6X7、8X10、10X12、12X14、14X17、17X19、19X22、22X24mm	8	1.18	
CL405510	6X7、8X10、9X11、10X12、12X14、14X17、17X19、19X22、22X24、24X27、30X32mm	10	2.36	
CL405512	6X7、8X10、9X11、10X12、13X15、12X14、14X17、17X19、18X21、19X22、22X24、24X27、30X32mm	12	2.62	
CL405514	6X7、8X10、9X11、10X12、11X13、13X15、12X14 、14X17、16X18、17X19、19X22、18X21、22X24、24X27、30X32mm	14	2.80	

- Forged with 40Cr steel, hardness HRC42~45°
- The surface is treated with electrophoretic rust prevention, and the clamp Angle is 15°
- For quick removal and fastening of hexagon bolts and nuts

Bi-hexagonal Ring Spanner Set



Item NO.	Size			RMB
CL403408	5.5X7、8X10、10X12、12X14、14X17、17X19、19X22、22X24mm	25	1.25	
CL403410	5.5X7、8X10、10X12、12X14、14X17、17X19、19X22、22X24、24X27、30X32mm	15	2.28	
CL403412	5.5X7、8X10、9X11、10X12、11X13、12X14、14X17 、17X19、19X22、22X24、 24X27、30X32mm	12	2.69	

- Forged by high carbon steel, hardness HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes

Electrophoretic Combination Spanner Set



Item NO.	Size			RMB
CL405408	8、9、10、12、13、14、17、19mm		0.74	
CL405410	8、9、10、11、12、13、14、17、19、22mm		1.19	
CL405412	6、7、8、9、10、11、12、13、14、17、19、22mm		1.24	
CL405414	8、9、10、11、12、13、14、15、16、17、18、19 22、24mm		1.97	

Electrophoresis Bi-hexagonal Ring Spanner Set



Item NO.	Size			RMB
CL405608	6X7、8X10、10X12、12X14、14X17 17X19、19X22、22X24mm	15	1.68	126.00
CL405610	6X7、8X10、10X12、12X14、14X17 17X19、19X22、22X24、24X27 30X32mm	6	3.01	
CL405612	6X7、8X10、9X11、10X12、12X14 14X17、17X19、18X21、19X22 22X24、24X27、30X32mm	5		

- Forged with 40Cr steel, hardness HRC42~45°
- The surface is treated with electrophoretic rust prevention
- For quick removal and fastening of hexagon bolts and nuts
- Head bend 45° to facilitate fastening and removing bolts in holes

14pcs Mirror Inch Combination Spanner Set



Item NO.	Size			RMB
CL405014	3/8、7/16、1/2、9/16、5/8、 11/16、3/4、13/16、7/8、 15/16、1、1-1/16、1-1/8、 1-1/4mm	6	3.97	

- It adopts high quality chromium-vanadium steel, the hardness is HRC42~45°
- Mirror polishing, chrome plating, rust-proof and wear-resistant treatment
- Bend the head 15° for easy fastening of dented hex bolts and nuts

24pcs Combination Spanner Set



Item NO.	Size			RMB
CL401324	6、7、8、9、10、11、12、13、14、15、 16、17、18、19、20、21、22、23、 24、26、27、28、30、32mm	4	5.66	

- Made of chromium-vanadium steel, the overall heat treatment hardness is HRC40~46°
- The surface is mirror polished, chrome plated and rust-proof
- Configuration 6-32mm made of Oxford fabric, beautiful and durable

15pcs Combination Spanner Set



Item NO.	Size			RMB
CL401315	8mm 9mm 10mm 11mm 12mm 13mm 14mm 15mm 16mm 17mm 18mm 19mm 21mm 22mm 24mm	8		

- Made of chromium-vanadium steel, the overall heat treatment hardness is HRC40~46°
- The surface is mirror polished, chrome plated and rust-proof
- Configuration 6-32mm made of Oxford fabric, beautiful and durable

VDE 绝缘

Full Polished Gear Combination Spanner



Item NO.	Size		RMB
CL400608	8mm	5/200	
CL400609	9mm	5/200	
CL400610	10mm	5/200	
CL400611	11mm	5/200	
CL400612	12mm	5/200	
CL400613	13mm	5/200	
CL400614	14mm	5/200	
CL400615	15mm	5/100	
CL400616	16mm	5/100	
CL400617	17mm	5/100	
CL400618	18mm	5/100	
CL400619	19mm	5/100	
CL400620	20mm	5/100	
CL400621	21mm	5/50	
CL400622	22mm	5/50	
CL400624	24mm	5/50	
CL400627	27mm	5/40	
CL400630	30mm	5/50	
CL400632	32mm	5/50	



Size	L	D	C	B	A	H	T	W kg
8mm	141	17.91	5.78	18.63	7.31	8.40	3.34	
9mm	149	19.12	5.60	20.07	7.50	8.50	3.27	
10mm	158	21.55	5.70	21.73	7.72	9.93	4.15	
11mm	164	23.55	6.10	22.64	8.28	10.41	4.15	
12mm	168	26.33	6.20	24.80	8.66	11.14	4.29	
13mm	177	27.12	6.93	26.37	9.00	12.67	5.23	
14mm	190	30.12	6.70	28.10	9.33	13.14	4.67	
15mm	198	32.20	7.61	30.31	9.74	14.04	5.42	
16mm	210	33.94	7.60	31.05	10.03	14.71	5.07	
17mm	225	35.72	8.08	32.50	10.66	15.43	5.27	
18mm	236	38.94	8.47	34.36	10.60	16.59	5.63	
19mm	247	40.56	8.72	36.34	11.12	17.26	6.07	
20mm	245	40.14	8.77	35.82	11.20	16.37	6.41	
21mm	289	45.08	9.34	42.61	13.30	19.22	6.270	
22mm	290	45.43	9.34	42.61	13.30	19.22	6.27	
24mm	334	52.17	11.00	49.25	14.53	22.36	7.33	
27mm	358	56.27	11.59	52.64	15.60	23.50	7.52	
30mm	401	61.90	12.70	57.28	17.34	26.31	8.56	
32mm	421	64.37	12.86	60.90	17.71	28.50	9.10	

- It adopts chrome-vanadium steel and 72 ratchet wheel design
- The surface is polished with mirror surface, rust-proof and beautiful
- 15° Angle offset, with direction button to switch forward reverse direction
- Professionally designed steering nuts with 5° action only
- Suitable for narrow space use and quick removal of long screw

Full Polished Adjustable Combination Spanner



Item NO.	Size		RMB
CL400708	8mm	10/100	
CL400709	9mm	10/150	
CL400710	10mm	10/100	
CL400711	11mm	10/100	
CL400712	12mm	10/100	
CL400713	13mm	10/100	
CL400714	14mm	10/100	
CL400715	15mm	10/100	
CL400716	16mm	10/100	
CL400717	17mm	10/100	
CL400718	18mm	10/100	
CL400719	19mm	10/100	
CL400722	22mm	10/50	
CL400724	24mm	6/48	



Size	L	D	C	B	A	H	T	W kg
8mm	145	21.30	5.50	20.50	7.90	9.96	3.60	
9mm	153	19.06	6.03	20.50	7.70	9.60	3.90	
10mm	163	21.30	5.82	22.00	7.68	10.14	3.90	
11mm	173	23.60	6.64	24.30	8.58	10.59	4.22	
12mm	185	26.61	7.30	25.26	9.02	11.60	4.50	
13mm	192	29.00	7.52	26.53	9.30	13.00	4.80	
14mm	188	29.25	7.05	28.18	9.24	13.15	4.54	
15mm	211	33.70	8.17	29.22	10.00	14.67	5.08	
16mm	220	35.73	8.78	30.75	10.54	15.33	5.96	
17mm	231	37.98	9.25	32.95	10.56	16.22	6.28	
18mm	243	40.55	9.03	34.85	11.00	17.59	6.66	
19mm	251	42.30	9.34	36.23	11.45	18.45	7.16	
22mm	281	48.10	10.20	42.34	13.66	20.01	6.88	
24mm	301	51.77	10.33	47.81	14.39	22.17	7.13	

- It adopts chrome-vanadium steel and 72 ratchet wheel design
- The surface is polished with mirror surface, rust-proof and beautiful
- Movable joint head, easy operation, professional design only 5° steering nut
- Suitable for narrow space use and quick removal of long screw

4pcs E Type Wrench




Item NO.	Size		RMB
CL404604	E6XE8mm E10XE12mm E14XE18mm E20XE24mm	4/40	

- Made of high quality vanadium steel, forged as a whole, with mirror processing
- Used for the removal and installation of E-nuts

Mirror Finish Bi-hexagonal Ring Ratchet Wrench



Item NO.	Size		RMB
CL402808	8-10mm	10/100	
CL400408	8-9mm	10/100	
CL400410	10-11mm	10/100	
CL400412	12-13mm	10/100	
CL400414	14-15mm	10/100	
CL400416	16-18mm	10/100	
CL400417	17-19mm	10/100	



Size	L	A	C	D	B	W kg
8-9mm	136	18.58	7.55	19.66	7.54	0.055
8-10mm	131	17.37	7.11	20.73	7.66	0.050
10-11mm	155	21.82	7.60	23.74	8.50	0.070
12-13mm	172	24.25	8.70	26.96	8.98	0.100
14-15mm	191	27.14	9.44	29.14	9.64	0.130
16-18mm	215	31.90	10.42	34.92	10.89	0.185
17-19mm	236	33.00	10.56	36.24	11.32	0.240

- It adopts chrome-vanadium steel and 72 ratchet wheel design
- The surface is polished with mirror surface, rust-proof and beautiful
- Easy operation, professional design only 5° steering nut
- Suitable for narrow space use and quick removal of long screw

The Movable Socket Combination Spanner



Item NO.	Size			RMB
CL402908	8mm	300	0.05	
CL402909	9mm	300	0.06	
CL402910	10mm	250	0.07	
CL402911	11mm	200	0.10	
CL402912	12mm	200	0.11	
CL402913	13mm	160	0.13	
CL402914	14mm	160	0.18	
CL402915	15mm	125	0.19	
CL402916	16mm	100	0.19	
CL402917	17mm	100	0.22	
CL402918	18mm	75	0.29	
CL402919	19mm	80	0.30	
CL402922	22mm	50	0.42	

- Cr-V forging and integral heat treatment
- The surface is treated with mirror chrome plating, beautiful and durable
- 25% longer than the average length of traditional spanner, more energy saving
- Used for automobile and machinery assembly and disassembly.
- Thin-walled sleeve and dual-use spanner make it easy to use

The Movable Double Head Socket Spanner



Item NO.	Size			RMB
CL403001	8X9mm	400	0.77	
CL403002	8X10mm	200	0.78	
CL403003	10X11mm	200	0.12	
CL403004	10X12mm	150	0.13	
CL403005	12X13mm	125	0.17	
CL403006	12X14mm	100	0.18	
CL403007	14X15mm	100	0.24	
CL403008	14X17mm	80	0.24	
CL403009	16X17mm	75	0.29	
CL403010	17X19mm	80	0.32	
CL403011	18X19mm	80	0.39	
CL403012	20X22mm	40	0.54	


- Cr-V forging and integral heat treatment
- The surface is treated with mirror chrome plating, beautiful and durable
- 25% longer than the average length of traditional spanner, more energy saving
- Used for automobile and machinery assembly and disassembly
- Thin wall sleeve, easy to use

Universal Wrench



Item NO.	Size			RMB
CL404701	2PCS	6/36	0.62	

- Double head specification: 9~14, 15~22mm, single head specification: 23~32mm;
- Made of high quality alloy steel forged by integral heat treatment;
- Easy to use, save wrench space, two-color handle, comfortable to use.



Open-End Knock Wrench



Item NO.	Size			RMB
CL410124	24mm	50	0.25	
CL410127	27mm	40	0.43	
CL410130	30mm	40	0.58	
CL410132	32mm	40	0.59	
CL410134	34mm	20	0.67	
CL410136	36mm	20	0.75	
CL410141	41mm	24	1.06	
CL410146	46mm	21	1.29	
CL410150	50mm	10	1.49	
CL410155	55mm	10	1.69	
CL410160	60mm	10	2.13	
CL410165	65mm	10	2.50	
CL410170	70mm	5	3.51	
CL410175	75mm	5	3.89	
CL410180	80mm	6	3.65	
CL410185	85mm	6	4.15	
CL410190	90mm	5	4.45	
CL410195	95mm	5	5.12	

- Forged with high quality alloy steel, thick and durable
- The surface is treated by electrophoresis, delicate and beautiful
- This product is an industrial grade tool

Single-head Open End Knock Wrench



Item NO.	Size			RMB
CL410324	24mm	50/件	0.24	
CL410327	27mm	50/件	0.31	
CL410330	30mm	50/件	0.45	
CL410332	32mm	50/件	0.43	
CL410334	34mm	40/件	0.64	
CL410336	36mm	40/件	0.65	
CL410341	41mm	20/件	1.12	
CL410346	46mm	20/件	1.32	
CL410350	50mm	10/件	1.50	
CL410355	55mm	20/件	1.43	
CL410360	60mm	10/件	2.42	
CL410365	65mm	10/件	2.35	
CL410370	70mm	5/件	3.11	
CL410375	75mm	5/件	3.11	

- Forged with high quality alloy steel, thick and durable
- The surface is blackened, delicate and beautiful
- Safety hole is designed for knocking end, which can be used for hanging wire, string, etc
- This product is an industrial grade tool

Single-head Ring Knock Wrench



Item NO.	Size			RMB
CL410224	24mm	50	0.27	
CL410227	27mm	65	0.38	
CL410230	30mm	40	0.58	
CL410232	32mm	40	0.59	
CL410234	34mm	32	0.67	
CL410236	36mm	35	0.75	
CL410241	41mm	24	1.06	
CL410246	46mm	21	1.29	
CL410250	50mm	18	1.49	
CL410255	55mm	16	1.69	
CL410260	60mm	10	2.13	
CL410265	65mm	10	2.50	
CL410270	70mm	5	3.51	
CL410275	75mm	6	3.89	
CL410280	80mm	6	3.66	
CL410285	85mm	6	4.15	
CL410290	90mm	5	4.82	
CL410295	95mm	5	4.62	
CL410200	100mm	1		
CL410205	105mm	3		
CL410210	110mm	1		
CL410215	115mm	1		
CL410220	120mm	1		

- Forged with high quality alloy steel, thick and durable
- The surface is treated by electrophoresis, delicate and beautiful
- This product is an industrial grade tool

Single-head Ring Wrench



Item NO.	Size			RMB
CL410424	24mm	50	0.32	
CL410427	27mm	40	0.39	
CL410430	30mm	40	0.60	
CL410432	32mm	40	0.64	
CL410434	34mm	40	0.58	
CL410436	36mm	40	0.70	
CL410441	41mm	20	1.15	
CL410446	46mm	20	1.39	
CL410450	50mm	10	1.34	
CL410455	55mm	10	1.83	
CL410460	60mm	10	1.72	
CL410465	65mm	10	1.98	
CL410470	70mm	5	2.34	
CL410475	75mm	5	2.77	

- Forged with high quality alloy steel, thick and durable
- The surface is blackened, delicate and beautiful
- This product is an industrial grade tool

Crescent Wrench



Item NO.	Size			RMB
CL410501	22-26mm		0.06	
CL410502	28-32mm		0.07	
CL410503	34-36mm		0.08	
CL410504	38-42mm		0.11	
CL410505	45-52mm		0.14	
CL410506	55-62mm		0.16	
CL410507	68-72mm		0.27	
CL410508	78-85mm		0.35	
CL410509	90-95mm		0.49	
CL410510	100-110mm		0.64	
CL410511	115-130mm		0.80	
CL410512	135-145mm		0.93	
CL410513	150-160mm		1.60	
CL410514	165-170mm		1.50	
CL410516	200-220mm			
CL410517	220-240mm			

- Made of special steel, tempered, hardened and rustproof by electrophoresis
- for round nuts according to DIN1084 and DIN981
- For fastening or disassembling round nuts on machine tools, vehicles and mechanical equipment



Single Ball Hex Key





Item NO.	Size	L(mm)	B(mm)			RMB
CL401701	1.5mm	92	16	12/96/1920	0.01	
CL401702	2mm	102	17	12/96/1920	0.01	
CL401725	2.5mm	104	21	12/96/1920	0.01	
CL401703	3mm	128	23	12/96/1920	0.01	
CL401704	4mm	146	27	10/70/1050	0.02	
CL401705	5mm	162	32	8/56/560	0.03	
CL401706	6mm	185	37	6/36/360	0.05	
CL401707	7mm	183	54	8/48/480	0.08	
CL401708	8mm	205	46	4/24/240	0.10	
CL401709	9mm	217	47	4/24/240	0.14	
CL401710	10mm	229	48	3/15/120	0.18	
CL401711	11mm	235	58	12/72	0.18	
CL401712	12mm	245	60	12/72	0.27	
CL401713	13mm	265	66	12/72	0.35	
CL401714	14mm	273	68	12/72	0.42	
CL401716	16mm	276	77	12/48	0.55	
CL401717	17mm	315	83	12/48	0.70	
CL401718	18mm	322	85	8/48	0.81	
CL401719	19mm	335	87	8/48	0.94	
CL401720	20mm	330	91	24	1.03	
CL401721	21mm	355	93	24	1.19	
CL401722	22mm	360	98	24	1.34	
CL401724	24mm	425	105	24	1.87	
CL401727	27mm	460	115	8	2.56	
CL401730	30mm	480	120	6	3.28	
CL401732	32mm	505	130	6	3.95	
CL401734	34mm	530	140	6	4.65	
CL401736	36mm	580	145	6	5.68	

- Made of high quality chromium-vanadium steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Fine sand nickel surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt

VDE
绝缘

Dual Color Handle Cane Type Ball Head Hex Key




Item NO.	Size	Entire length	Rod length	Head length			RMB
CL407525	2.5mm	137mm	98mm	85mm	20/400	0.03	
CL407502	2mm	137mm	98mm	85mm	20/400	0.03	
CL407503	3mm	137mm	98mm	85mm	20/400	0.03	
CL407504	4mm	184mm	142mm	94mm	16/320	0.07	
CL407505	5mm	185mm	144mm	92mm	16/320	0.07	
CL407506	6mm	198mm	158mm	95mm	12/240	0.07	
CL407508	8mm	255mm	200mm	126mm	12/120	0.20	
CL407510	10mm	256mm	200mm	130mm	12/120	0.28	

- Made of high-quality chromium vanadium steel, with overall heat treatment.
- The tail end ball head design can be tilted 25 degrees for use, used for disassembling and tightening internal hexagonal bolts.
- Designed according to ergonomics, the handle is comfortable to grip and effectively prevents slipping.

Cane Type Ball Head Hex Key



DIN Cr-V




Item NO.	Size	L(mm)	B(mm)	A(mm)	D(mm)			RMB
CL404002	2mm	145	90	14	92	100/400	0.02	
CL404025	2.5mm	148	90	13	93	100/400	0.03	
CL404003	3mm	154	90	13	99	20/400	0.03	
CL404004	4mm	156	90	13	101	100/500	0.04	
CL404005	5mm	215	112	16	147	20/200	0.08	
CL404006	6mm	215	110	15	147	20/200	0.09	
CL404007	7mm	208	92	17	150	20/100	0.11	
CL404008	8mm	260	112	17	193	20/100	0.16	
CL404010	10mm	275	112	17	196	20/100	0.27	

- Made of high quality chromium-vanadium steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Chrome plated surface, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt
- L type wrench is comfortable to hold and effective to prevent slip

Cane Type Ball Head Hex Key



DIN Cr-V




Item NO.	Size	L(mm)	B(mm)	A(mm)	D(mm)			RMB
CL406603	3X75mm	101	85	14	76	10/200	0.03	
CL406604	4X100mm	125	86	16	100	10/200	0.04	
CL406605	5X125mm	160	116	17	125	10/200	0.09	
CL406606	6X150mm	186	116	16	150	10/100	0.11	
CL406608	8X175mm	214	120	18	176	10/100	0.16	

- Made of 40Cr steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Fine sand nickel surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt

Torx Wrench Mirror Cane Type Ball Head Hex Key



Cr-V



Item NO.	Size	L(mm)	B(mm)	A(mm)	D(mm)			RMB
CL404410	T10	146	70	14	100	20/400	0.02	
CL404415	T15	146	70	14	100	20/400	0.03	
CL404420	T20	150	70	15	102	20/400	0.03	
CL404425	T25	150	70	14	105	20/400	0.04	
CL404427	T27	213	90	16	153	20/200	0.07	
CL404430	T30	210	92	17	150	20/200	0.08	
CL404440	T40	212	92	17	150	20/100	0.10	
CL404445	T45	275	112	17	195	20/100	0.18	
CL404450	T50	280	112	16	197	20/100	0.21	

- Meet CAMCAR original factory standard manufacturing requirements
- Made of high quality chromium-vanadium steel with integral heat treatment
- Used to remove and tighten TORX star bolts
- Chrome plated surface, beautiful and wear-resistant
- L type wrench is comfortable to hold and effective to prevent slip

G17 Type 9pcs Mat Finish Ball head Hex Key Set



Item NO.	Size			RMB
CL406502	medium	12 / 60	0.38	
CL406503	Lengthen	12 / 60	0.46	

- Made of 40Cr steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Fine sand nickel surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt
- Configuration: 1.5 2 2.5 3 4 5 6 8 10

9pcs Mat Finish Star Type Hex Key Set



Item NO.	Size			RMB
CL402001	normal	10/50	0.29	
CL402002	medium	10/50	0.36	
CL402003	Lengthen	10/50	0.46	

- Meet CAMCAR original factory standard manufacturing requirements
- Made of high quality 6150 chrome-vanadium steel with integral heat treatment
- Used to remove and tighten TORX star bolts
- Fine sand nickel butyl surface treatment, beautiful and wear-resistant
- Configuration: T10 T15 T20 T25 T27 T30 T40 T45 T50

G17 Mat Finish Star Type Hex Key Set



Item NO.	Size			RMB
CL406512	medium	10/60		
CL406513	Lengthen	10/60		

- Made of 40Cr steel and subjected to overall heat treatment.
- Fine sand nickel surface treatment, beautiful and wear-resistant, with complete size and convenient use.
- Used for disassembling and tightening inner star bolts.
- Configuration: T10 T15 T20 T25 T27 T30 T40 T45 T50

9pcs Mirror Finish Ball Hex Key Set



Item NO.	Size			RMB
CL402101	normal	10/50	0.27	
CL402102	medium	10/50	0.39	
CL402103	Lengthen	10/50	0.45	

- Made of high quality 6150 chrome-vanadium steel with integral heat treatment
- Used to remove and tighten hexagon socket bolts
- Chrome plated surface, beautiful and wear-resistant
- The ball head can be used at a 25 degree tilt
- Configuration: 1.5 2 2.5 3 4 5 6 8 10

9pcs Mat Finish Ball Hex Key Set



Item NO.	Size			RMB
CL401901	normal	10/50		
CL401902	medium	10/50		
CL403801	medium (British system)	10/50		
CL401903	Lengthen	10/50	0.48	

- Made of high quality 6150 chrome-vanadium steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Fine sand nickel surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt
- Configuration: 1.5 2 2.5 3 4 5 6 8 10



VDE
绝缘

9pcs Mirror Finish Star Type Hex Key Set



Cr-V

Item NO.	Size			RMB
CL402013	Lengthen	10/60	0.45	

- Meet CAMCAR original factory standard manufacturing requirements
- Made of high quality 6150 chrome-vanadium steel with integral heat treatment
- Used to remove and tighten TORX star bolts
- Chrome plated surface, beautiful and wear-resistant
- Configuration: T10 T15 T20 T25 T27 T30 T40 T45 T50

9pcs Bronze Ball Hex Key Set



DIN S2

Item NO.	Size			RMB
CL402202	medium	10/50	0.40	
CL402203	Lengthen	10/50	0.49	

- Comply with DIN 2936 standard manufacturing requirements
- Made of S2 material with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Bronze surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt
- Configuration: 1.5 2 2.5 3 4 5 6 8 10

13pcs Mat Finish Ball Hex Key Set



DIN Cr-V

Item NO.	Size			RMB
CL407013	13PCS	12/48	0.51	

- Made of 6150 chromium molybdenum steel with integral heat treatment
- The tail ball head is designed for removing and fastening hexagon socket bolts
- Fine sand nickel surface treatment, beautiful and wear-resistant, spherical wrench can be used at a 25 degree tilt
- Configuration: 1.27 1.5 2 2.5 3 4 4.5 5 5.5 6 7 8 11

8pcs Folding type Flat Type Hex Key Set



DIN Cr-V

Item NO.	Size			RMB
CL406701	8PCS	12/60	0.20	

- Made of 6150 chromium-vanadium steel with integral heat treatment
- Folding handle is comfortable to hold and effective to prevent slip
- Used to remove and tighten hexagon socket bolts
- Fine sand nickel butyl surface treatment, beautiful and wear-resistant
- Configuration: 1.5 2 2.5 3 4 5 6 8

9pcs Black Finish Flat Hex Key Set



DIN Cr-V

Item NO.	Size			RMB
CL402212	medium	10/50	0.37	

- Made of high quality chromium-vanadium steel with integral heat treatment
- Used to remove and tighten hexagon socket bolts
- Black surface treatment, beautiful and wear-resistant
- Configuration: 1.5 2 2.5 3 4 5 6 8 10

8pcs Folding type Star Type Hex Key Set



Item NO.	Size			RMB
CL406702	8PCS	12/60	0.19	

- Meet CAMCAR original factory standard manufacturing requirements
- Made of 6150 chromium-vanadium steel with integral heat treatment
- Used to remove and tighten TORX star bolts
- Fine sand nickel butyl surface treatment, beautiful and wear-resistant
- Folding handle is comfortable to hold and effective to prevent slip
- Configuration: T9 T10 T15 T20 T25 T27 T30 T40